

# n-Hexane C<sub>6</sub>H<sub>14</sub>

Cylinder Pressure  
 108 ..... 240 psig (17 bar)  
 All Others ..... 2000 psig (138 bar)  
 Cylinder Valve Outlet CGA No.  
 in Air ..... 590  
 in N<sub>2</sub> in 108 ..... 510  
 in N<sub>2</sub> in all Others ..... 350  
 DOT/TC Label ..... Nonflammable  
 Other Available Sizes .... SCOTTY™ Transportable

**Recommended Equipment**  
 Two-Stage Regulator ..... Model 318, Page 270  
 Single-Stage Regulator .... Model 3300, Page 270  
 Single-Station Manifold .... Model 8100, Page 309

in HC-Free Air				Dual-Certified Standards	Single-Certified Standards		
				Gravstat	Acublend	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Master Class	Working Class
		CF	m <sup>3</sup>				
ACULIFE 10 – 999 ppb*	30AL	144	4				•
	16AL	76	2				•
	7AL	29	0.8				•
1 – 49 ppm	30AL	144	4	•	•	•	•
	16AL	76	2	•	•	•	•
	7AL	29	0.8	•	•	•	•
50 – 5000 ppm**	44	214	6	•	•	•	•
	16	84	2	•	•	•	•
	7	33	0.9	•	•	•	•

in Nitrogen				Dual-Certified Standards	Single-Certified Standards		
				Gravstat	Acublend	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Master Class	Working Class
		CF	m <sup>3</sup>				
ACULIFE 10 – 999 ppb*	30AL	140	4			•	•
	16AL	74	2			•	•
	7AL	28	0.8			•	•
1 – 49 ppm	30AL	140	4	•	•	•	•
	16AL	74	2	•	•	•	•
	7AL	28	0.8	•	•	•	•
50 – 5000 ppm**	44	209	6	•	•	•	•
	16	82	2	•	•	•	•
	7	32	0.9	•	•	•	•
	108	66	2	•	•	•	•

\* Contact your Air Liquide representative for available MICROGRAV™ ppt mixtures and recommended equipment.

\*\* Cylinder pressure and contents will vary.

Through its technological advancements, only Air Liquide offers ppb hexane calibration standards with guaranteed stability.