

Dimethyl Disulfide $\text{CH}_3\text{S}_2\text{CH}_3$

Cylinder Pressure 2000 psig (138 bar)
 Cylinder Valve Outlet CGA No. 350
 DOT/TC Label Nonflammable
 Other Available Sizes SCOTTY™ Transportable

Recommended Equipment
 Two-Stage Regulator Model 215, Page 271
 Single-Stage Regulator Model 213, Page 271

in Nitrogen				Single-Certified Standards	
				Certified	
Concentration	Size	Contents		Master Class	Working Class
		CF	m ³		
ACULIFE 0.1 – 0.9 ppm	30AL	140	4		•
	16AL	74	2		•
	7AL	28	0.8		•
ACULIFE 1 – 9 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
ACULIFE 10 – 49 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
ACULIFE 50 – 999 ppm*	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•

* Cylinder pressure and contents will vary.

Through its technological advancements, only Air Liquide offers sub-ppm dimethyl disulfide calibration standards with guaranteed stability.