

# Ethylene Oxide C<sub>2</sub>H<sub>4</sub>O

Cylinder Pressure ..... 2000 psig (138 bar)  
 Cylinder Valve Outlet CGA No. .... 350  
 DOT/TC Label ..... Nonflammable  
 Other Available Sizes ..... Please Inquire

**Recommended Equipment**  
 Two-Stage Regulator ..... Model 215, Page 271  
 Single-Stage Regulator ..... Model 213, Page 271  
 Single-Station Manifold .... Model 8100, Page 309

in Nitrogen				Single-Certified Standards	
				Certified	
Concentration	Size	Contents		Master Class	Working Class
		CF	m <sup>3</sup>		
ACULIFE 1 – 5 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
ACULIFE 5.1 – 99 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
100 – 999 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
0.1 – 2%*	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•

\* Cylinder pressure and contents will vary.

Through its technological advancements, only Air Liquide offers ppm ethylene oxide calibration standards with guaranteed stability.