

# Methyl Mercaptan CH<sub>3</sub>SH

Cylinder Pressure ..... 2000 psig (138 bar)  
 Cylinder Valve Outlet CGA No. .... 330  
 DOT/TC Label  
   in CH<sub>4</sub> ..... Flammable  
   in N<sub>2</sub> ..... Nonflammable  
 Other Available Sizes .... SCOTTY™ Transportable

**Recommended Equipment**  
 Two-Stage Regulator ..... Model 215, Page 271  
 Single-Stage Regulator ..... Model 213, Page 271

in Methane				Single-Certified Standards	
				Certified	
Concentration	Size	Contents		Master Class	Working Class
		CF	m <sup>3</sup>		
ACULIFE 0.1 – 1 ppm†	30AL	175	5	•	•
	16AL	93	3	•	•
	7AL	35	1	•	•
ACULIFE 1.1 – 49 ppm	30AL	175	5	•	•
	16AL	93	3	•	•
	7AL	35	1	•	•
ACULIFE 50 – 999 ppm	30AL	175	5	•	•
	16AL	93	3	•	•
	7AL	35	1	•	•
ACULIFE 0.1 – 1%†	30AL	*	*	•	•
	16AL	*	*	•	•
	7AL	*	*	•	•

in Nitrogen				Single-Certified Standards	
				Certified	
Concentration	Size	Contents		Master Class	Working Class
		CF	m <sup>3</sup>		
ACULIFE 0.1 – 1 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
ACULIFE 1.1 – 49 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
ACULIFE 50 – 999 ppm	30AL	140	4	•	•
	16AL	74	2	•	•
	7AL	28	0.8	•	•
ACULIFE 0.1 – 1%†	30AL	*	*	•	•
	16AL	*	*	•	•
	7AL	*	*	•	•

\* Cylinder pressure and contents will vary.

† Not available in SCOTTY™ Transportable cylinders.

Methyl mercaptan calibration standards are also available in hydrocarbon balance gases. Contact your Air Liquide representative for more information.