

Nitrogen N₂

Cylinder Pressure 2000 psig (138 bar)
 Cylinder Valve Outlet CGA No. 580
 DOT/TC Label Nonflammable
 Other Available Sizes SCOTTY™ Transportable

Recommended Equipment
 Two-Stage Regulator Model 318, Page 270
 Single-Stage Regulator Model 3300, Page 270
 Single-Station Manifold Model 8100, Page 309

in Argon				Dual-Certified Standards	Single-Certified Standards	
				Gravstat	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Working Class
		CF	m ³			
10 – 49 ppm	44	225	6	•	•	•
	16	89	3	•	•	•
	7	35	1	•	•	•
50 – 999 ppm	44	225	6	•	•	•
	16	89	3	•	•	•
	7	35	1	•	•	•
0.1 – 49%	44	221	6	•	•	•
	16	87	3	•	•	•
	7	34	1	•	•	•

in Helium				Dual-Certified Standards	Single-Certified Standards	
				Gravstat	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Working Class
		CF	m ³			
10 – 49 ppm	44	199	6	•	•	•
	16	78	2	•	•	•
	7	31	0.9	•	•	•
50 – 999 ppm	44	199	6	•	•	•
	16	78	2	•	•	•
	7	31	0.9	•	•	•
0.1 – 49%	44	200	6	•	•	•
	16	79	2	•	•	•
	7	31	0.9	•	•	•