

Sulfur Hexafluoride SF₆

Cylinder Pressure 2000 psig (138 bar)
 Cylinder Valve Outlet CGA No.
 in Air 590
 in N₂ 580
 DOT/TC Label Nonflammable
 Other Available Sizes SCOTTY™ Transportable

Recommended Equipment
 Two-Stage Regulator Model 318, Page 270
 Single-Stage Regulator Model 3300, Page 270
 Single-Station Manifold Model 8100, Page 309

in Air				Dual-Certified Standards	Single-Certified Standards	
				Gravstat	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Working Class
		CF	m ³			
10 ppb – 0.99 ppm*	30AL	144	4		•	•
	16AL	76	2		•	•
	7AL	29	0.8		•	•
1 – 99 ppm*	30AL	144	4	•	•	•
	16AL	76	2	•	•	•
	7AL	29	0.8	•	•	•
100 ppm – 1%	44	214	6	•	•	•
	16	84	2	•	•	•
	7	33	0.9	•	•	•

in Nitrogen				Dual-Certified Standards	Single-Certified Standards	
				Gravstat	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Working Class
		CF	m ³			
10 ppb – 0.99 ppm*	30AL	140	4		•	•
	16AL	74	2		•	•
	7AL	28	0.8		•	•
1 – 99 ppm*	30AL	140	4	•	•	•
	16AL	74	2	•	•	•
	7AL	28	0.8	•	•	•
100 ppm – 1%	44	209	6	•	•	•
	16	82	2	•	•	•
	7	32	0.9	•	•	•

* Contact your Air Liquide Representative for available MICROGRAV™ ppt mixtures and recommended equipment.