

Vinyl Chloride CH₂:CHCl

Cylinder Pressure 2000 psig (138 bar)
 Cylinder Valve Outlet CGA No.
 in Air 590
 in N₂ 350
 DOT/TC Label Nonflammable
 Other Available Sizes SCOTTY™ Transportable

Recommended Equipment
 Two-Stage Regulator Model 318, Page 270
 Single-Stage Regulator Model 3300, Page 270
 Single-Station Manifold Model 8100, Page 309

in Air				Dual-Certified Standards	Single-Certified Standards	
				Gravstat	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Working Class
		CF	m ³			
ACULIFE 0.1 – 9 ppm	30AL	144	4		•	•
	16AL	76	2		•	•
	7AL	29	0.8		•	•
ACULIFE 10 – 49 ppm	30AL	144	4		•	•
	16AL	76	2		•	•
	7AL	29	0.8		•	•
ACULIFE 50 – 2000 ppm	30AL	144	4	•	•	•
	16AL	76	2	•	•	•
	7AL	29	0.8	•	•	•

in Nitrogen				Dual-Certified Standards	Single-Certified Standards	
				Gravstat	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Working Class
		CF	m ³			
ACULIFE 0.1 – 9 ppm	30AL	140	4		•	•
	16AL	74	2		•	•
	7AL	28	0.8		•	•
ACULIFE 10 – 49 ppm	30AL	140	4		•	•
	16AL	74	2		•	•
	7AL	28	0.8		•	•
ACULIFE 50 – 2000 ppm	30AL	140	4	•	•	•
	16AL	74	2	•	•	•
	7AL	28	0.8	•	•	•