

# n-Pentane C<sub>5</sub>H<sub>12</sub>

Cylinder Pressure  
 108 ..... 240 psig (17 bar)  
 All Others ..... 2000 psig (138 bar)  
 Cylinder Valve Outlet CGA No.  
 in Air ..... 590  
 in N<sub>2</sub> in 108 ..... 510  
 in N<sub>2</sub> all Others ..... 350  
 DOT/TC Label ..... Nonflammable  
 Other Available Sizes .... SCOTTY™ Transportable

**Recommended Equipment**  
 Two-Stage Regulator ..... Model 318, Page 270  
 Single-Stage Regulator .... Model 3300, Page 270  
 Single-Station Manifold .... Model 8100, Page 309

in HC-Free Air				Dual-Certified Standards	Single-Certified Standards		
				Gravstat	Acublend	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Master Class	Working Class
		CF	m <sup>3</sup>				
1 – 49 ppm	44	214	6	•	•	•	•
	16	84	2	•	•	•	•
	7	33	0.9	•	•	•	•
50 – 6000 ppm*	44	214	6	•	•	•	•
	16	84	2	•	•	•	•
	7	33	0.9	•	•	•	•

in Nitrogen				Dual-Certified Standards	Single-Certified Standards		
				Gravstat	Acublend	Certified	
Concentration	Size	Contents		Reference Class	Master Class	Master Class	Working Class
		CF	m <sup>3</sup>				
1 – 49 ppm	44	209	6	•	•	•	•
	16	82	2	•	•	•	•
	7	32	0.9	•	•	•	•
50 ppm – 1%*	44	209	6	•	•	•	•
	16	82	2	•	•	•	•
	7	32	0.9	•	•	•	•
	108	80	2	•	•	•	•

\* Cylinder pressure and contents will vary.